


## KOMBIC 70 SURFACE

K71SF1520RF940D66



## KOMBIC 70 SF 1500 IP23 940 RF FL D SER

**Description:**

Downlight for surface mount or suspension model KOMBIC 70 SF 1500. Body made of recycled aluminum extrusion with a rate of 75% and reflector made of recycled polycarbonate R-PC FR WHITE TM with bromine-free flame retardant. Flammability grade V0 according to UL94. Flood reflector for greater efficiency and control of light distribution and low glare UGR<16. Heat sink made of aluminum injection. LED COB, with color temperature 4000K with CRI90. DALI electronic equipment included. With a protection degree of IP23. Insulation class I. Photobiological safety group 0. Lifespan: 72,000 L80 B10. Available finish SERENA palette (Arena, Bronze, Champagne, Dark Chocolate, Dark Grey, Terracotta). Tolerance of luminous flux  $\pm 4\%$  according to finish.

**Weight:** 570 g**Installation:** Surface**TECHNICAL SPECIFICATIONS:**

<b>Plum:</b>	10,8W	<b>°K :</b>	4000
<b>UGR:</b>	19	<b>CRI :</b>	90
<b>Type:</b>	COB	<b>R9 :</b>	71
<b>LED Lifetime:</b>	72.000 L80 B10 (Ta=25°C)	<b>MacAdam:</b>	3
		<b>Power Supply:</b>	220-240V 50/60Hz
		<b>Gear:</b>	Adjustable DALI

**CUSTOM MADE OPTIONS:**

KOMBIC 70 SURFACE

ACCESORIES :

Suspension



Product code:

K71SUCAWI2000D66

Description:

KOMBIC 70 SF ACC. ELEC 5P SUSP 2M SMS