


## KOMBIC 70 SURFACE

K71SF1540OP830N66



## KOMBIC 70 SF 1500 IP40 830 OPAL SER

**Description:**

Downlight for surface mount or suspension model KOMBIC 70 SF 1500. Body made of recycled aluminum extrusion with a rate of 75% and reflector made of recycled polycarbonate R-PC FR WHITE TM with bromine-free flame retardant. Flammability grade V0 according to UL94. Opal optical film. Heat sink made of aluminum injection. LED COB, with color temperature 3000K with CRI80. ON OFF electronic equipment included. With a protection degree of IP43. Insulation class I. Photobiological safety group 0. Lifespan: 72,000 L80 B10. Available finish SERENA palette (Arena, Bronze, Champagne, Dark Chocolate, Dark Grey, Terracotta). Tolerance of luminous flux  $\pm 7\%$  according to finish.

**Weight:** 510 g**Installation:** Surface**TECHNICAL SPECIFICATIONS:**

<b>Plum:</b>	9,5W	<b>°K :</b>	3000
<b>Type:</b>	COB	<b>CRI :</b>	80
<b>LED Lifetime:</b>	72.000 L80 B10 (Ta=25°C)	<b>MacAdam:</b>	3
		<b>Power Supply:</b>	220-240V 50/60Hz
		<b>Gear:</b>	Electronic

**CUSTOM MADE OPTIONS:**

KOMBIC 70 SURFACE

ACCESORIES :

Suspension



Product code:

K71SUCAWI2000N66

Description:

KOMBIC 70 SF ACC. ELEC 3P SUSP 2M SMS