


KOMBIC 70 SURFACE

K71SF1540OP930D66



KOMBIC 70 SF 1500 IP40 930 OPAL D SER

Description:

Downlight for surface mount or suspension model KOMBIC 70 SF 1500. Body made of recycled aluminum extrusion with a 75% rate and reflector made of recycled polycarbonate R-PC FR WHITE TM with bromine-free flame retardant. Flammability grade V0 according to UL94. Opal optical film. Heat sink made of aluminum injection. LED COB, with color temperature 3000K with CRI90. DALI electronic equipment included. With an IP43 protection rating. Insulation class I. Photobiological safety group 0. Lifespan: 72,000 L80 B10. Available finish SERENA palette (Arena, Bronze, Champagne, Dark Chocolate, Dark Grey, Terracotta). Tolerance of luminous flux $\pm 7\%$ according to finish.

Weight: 570 g**Installation:** Surface**TECHNICAL SPECIFICATIONS:**

Plum:	10,8W	°K :	3000
Type:	COB	CRI :	90
LED Lifetime:	72.000 L80 B10 (Ta=25°C)	R9 :	54
		MacAdam:	3
		Power Supply:	220-240V 50/60Hz
		Gear:	Adjustable DALI

**CUSTOM MADE OPTIONS:**

KOMBIC 70 SURFACE

ACCESORIES :

Suspension



Product code:

K71SUCAWI2000D66

Description:

KOMBIC 70 SF ACC. ELEC 5P SUSP 2M SMS