KOMBIC 70 SURFACE



K71SF1540OP940NWW



KOMBIC 70 SF 1500 IP43 9NW OP W/W

Description:

LAMP Suspended or ceiling mounting downlight KOMBIC 70 SF 1500. Body made of recycled aluminium extrusion at a rate of 75% and reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Inner reflector finished in white and opal optical film. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K and IRC90. Electronic ON OFF gear included. IP43 rated. Insulation Class I. Photobiological safety group 0. LED life time: 72.000 L80 B10. White finish.



Finish: Matte white RAL 9010

Weight: 510 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 849 lm °K: 4000 Plum: 9,5W CRI: 90 Efficacy: 89,4 lm/w 3 MacAdam:

Type: СОВ Power Supply: 220-240V 50/60Hz

LED Lifetime: 72.000 L80 B10 (Ta=25°C) Gear: Electronic

8,4W Power:

Light output tolerance +/- 10%



CLASE





















CUSTOM MADE OPTIONS:

















KOMBIC 70 SURFACE




K71SF1540OP940NWW


KOMBIC 70 SF 1500 IP43 9NW OP W/W


PHOTOMETRIC DATA:


K71SF1540OP940NWW η = 100% lmax = 942 cd/klmUTE: 1,00B


CIE: 75 94 99 100 100




















KOMBIC 70 SURFACE



ACCESORIES:

Suspension



Product code:

K71SUADLATBK



KOMBIC 70 SF ADAPT. LATERAL CABLE BK



Product code:

K71SUADLATWH

Description:

KOMBIC 70 SF ADAPT. LATERAL CABLE WH



Product code:

K71SUCAWI2000DBK K71SUCAWI2000NBK

Description:

KOMBIC 70 SF ACC. ELEC 5P SUSP 2M BK KOMBIC 70 SF ACC. ELEC 3P SUSP 2M BK



Product code:

K71SUCAWI2000DWH K71SUCAWI2000NWH

Description:

KOMBIC 70 SF ACC. ELEC 5P SUSP 2M WH KOMBIC 70 SF ACC. ELEC 3P SUSP 2M WH