


KOMBIC 70 SURFACE

K71SF1540WF930N66



KOMBIC 70 SF 1500 IP43 930 WFL SER

Description:

Downlight for surface mount or suspension model KOMBIC 70 SF 1500. Body made of recycled aluminum extrusion with a 75% rate and reflector made of recycled polycarbonate R-PC FR WHITE TM with bromine-free flame retardant. Flammability grade V0 according to UL94. Wide flood optics with control of light distribution and low glare UGR<16. Heat sink made of aluminum injection. LED COB, with color temperature 3000K with CRI90. ON OFF electronic equipment included. With a protection degree of IP43. Insulation class I. Photobiological safety group 0. Lifespan: 72,000 L80 B10. Available finish SERENA palette (Arena, Bronze, Champagne, Dark Chocolate, Dark Grey, Terracotta). Tolerance of luminous flux $\pm 5\%$ according to finish.

Weight: 530 g**Installation:** Surface**TECHNICAL SPECIFICATIONS:**

Plum:	9,5W	°K :	3000
UGR:	19	CRI :	90
Type:	COB	R9 :	54
LED Lifetime:	72.000 L80 B10 (Ta=25°C)	MacAdam:	3
		Power Supply:	220-240V 50/60Hz
		Gear:	Electronic

**CUSTOM MADE OPTIONS:**

KOMBIC 70 SURFACE

ACCESORIES :

Suspension



Product code:

K71SUCAWI2000N66

Description:

KOMBIC 70 SF ACC. ELEC 3P SUSP 2M SMS