


K71ST1520RF927N66

**KOMBIC 70 SUT 1500 IP20 927 RF FL SER****Description:**

Downlight to suspend from a three-phase track model KOMBIC 70 ST 1500. Body made of recycled aluminum extrusion with a 75% rate and reflector made of recycled polycarbonate R-PC FR WHITE TM with bromine-free flame retardant. Flammability grade V0 according to UL94. Flood reflector for greater efficiency and control of light distribution and lower glare UGR<16. Heat sink made of aluminum injection. LED COB, with color temperature 2700K with CRI90. ON OFF electronic equipment included. With a protection degree of IP20. Insulation class II. Photobiological safety group 0. Lifespan: 72,000 L80 B10. Available finish SERENA palette (Arena, Bronze, Champagne, Dark Chocolate, Dark Grey, Terracotta). Tolerance of luminous flux $\pm 4\%$ according to finish.

Weight: 610 g**Installation:** Suspended**TECHNICAL SPECIFICATIONS:**

Plum:	10,5W	°K :	2700
UGR:	19	CRI :	90
Type:	COB	MacAdam:	3
LED Lifetime:	72.000 L80 B10 (Ta=25°C)	Power Supply:	220-240V 50/60Hz
Power:	8,4W	Gear:	Electronic

**CUSTOM MADE OPTIONS:**