

KOMBIC 70 SUT

K71ST1520RW927D66



KOMBIC 70 SUT 1500 IP20 927 RF WFL D SER

Description:

Downlight to suspend on a three-phase track model KOMBIC 70 ST 1500. Body made of recycled aluminum extrusion with a rate of 75% and reflector of recycled polycarbonate R-PC FR WHITE TM with bromine-free flame retardant. Flammability grade V0 according to UL94. Heat sink made of aluminum injection. LED COB, with color temperature 2700K with CRI90. DALI electronic equipment included. With a protection degree of IP20. Insulation class II. Photobiological safety group 0. Lifespan: 72,000 L80 B10. Available finish SERENA palette (Arena, Bronze, Champagne, Dark Chocolate, Dark Grey, Terracotta). Tolerance of luminous flux $\pm 4\%$ according to finish.

Weight: 650 g**Installation:** Suspended**TECHNICAL SPECIFICATIONS:**

Plum:	10,3W	°K :	2700
UGR:	19	CRI :	90
Type:	COB	MacAdam:	3
LED Lifetime:	72.000 L80 B10 (Ta=25°C)	Power Supply:	220-240V 50/60Hz
Power:	8,4W	Gear:	Adjustable DALI

**CUSTOM MADE OPTIONS:**