

KOMBIC 70 SUT

K71ST1520RW940DWW



KOMBIC 70 SUT 1500 IP20 9NW RF WFL D W/W

Description:

LAMP Suspended or ceiling mounting downlight KOMBIC 70 SUT 1500. Body made of recycled aluminium extrusion at a rate of 75% and reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Inner reflector finished in white and Wide Flood reflector for greater efficiency and to achieve controlled light distribution and low glare level, less than UGR<19. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K and IRC90. Electronic DALI gear included. IP20 rated. Insulation Class II. Photobiological safety group 0. LED life time: 72.000 L80 B10. Available finishes: White and black.

Finish: Matte white RAL 9010

Weight: 650 g

Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output:	1.002 lm	°K :	4000
Plum:	10,3W	CRI :	90
Efficacy:	97,3 lm/w	R9 :	71
UGR:	19	MacAdam:	3
Type:	COB	Power Supply:	220-240V 50/60Hz
LED Lifetime:	72.000 L80 B10 (Ta=25°C)	Gear:	Adjustable DALI
Power:	8,4W		

Light output tolerance +/- 10%


CUSTOM MADE OPTIONS:



K71ST1520RW940DWW

KOMBIC 70 SUT 1500 IP20 9NW RF WFL D W/W

PHOTOMETRIC DATA :

