


KOMBIC 70 SUT

K71ST1540OP830NWW



KOMBIC 70 SUT 1500 IP40 WW OP W/W

Description:

LAMP Suspended or ceiling mounting downlight KOMBIC 70 SUT 1500. Body made of recycled aluminium extrusion at a rate of 75% and reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Inner reflector finished in white and opal optical film. Heatsink made of die-cast aluminium. COB LED, colour temperature 3000K and IRC80. Electronic ON OFF gear included. IP40 rated. Insulation Class II. Photobiological safety group 0. LED life time: 72.000 L80 B10. White finish.

Finish: Matte white RAL 9010

Weight: 610 g

Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output:	935 lm	°K :	3000
Plum:	10,5W	CRI :	80
Efficacy:	89 lm/w	MacAdam:	3
Type:	COB	Power Supply:	220-240V 50/60Hz
LED Lifetime:	72.000 L80 B10 (Ta=25°C)	Gear:	Electronic
Power:	8,4W		

Light output tolerance +/- 10%


CUSTOM MADE OPTIONS:



K71ST1540OP830NWW

KOMBIC 70 SUT 1500 IP40 WW OP W/W

PHOTOMETRIC DATA :

