

K71ST1540OP927D66

**KOMBIC 70 SUT 1500 IP40 927 OPAL D SER****Description:**

Downlight to suspend from a three-phase track model KOMBIC 70 ST 1500. Body made of recycled aluminum extrusion with a 75% rate and reflector of recycled polycarbonate R-PC FR WHITE TM with bromine-free flame retardant. Flammability grade V0 according to UL94. Opal optical film. Heat sink made of aluminum injection. LED COB, with color temperature 2700K with CRI90. DALI electronic equipment included. With an IP40 protection rating. Insulation class II. Photobiological safety group 0. Lifespan: 72,000 L80 B10 hours. Available finish SERENA palette (Arena, Bronze, Champagne, Dark Chocolate, Dark Grey, Terracotta). Tolerance of luminous flux  $\pm 7\%$  according to finish.

**Weight:** 650 g**Installation:** Suspended**TECHNICAL SPECIFICATIONS:**

<b>Type:</b>	COB	<b>°K :</b>	2700
<b>LED Lifetime:</b>	72.000 L80 B10 (Ta=25°C)	<b>CRI :</b>	90
<b>Power:</b>	8,4W	<b>MacAdam:</b>	3
		<b>Power Supply:</b>	220-240V 50/60Hz
		<b>Gear:</b>	Adjustable DALI

**CUSTOM MADE OPTIONS:**