


## KOMBIC 70 SUT

K71ST1540OP927DWW



## KOMBIC 70 SUT 1500 IP40 9VWW OP D W/W

**Description:**

LAMP Suspended or ceiling mounting downlight KOMBIC 70 SUT 1500. Body made of recycled aluminium extrusion at a rate of 75% and reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Inner reflector finished in white and opal optical film. Heatsink made of die-cast aluminium. COB LED, colour temperature 2700K and IRC90. Electronic DALI gear included. IP40 rated. Insulation Class II. Photobiological safety group 0. LED life time: 72.000 L80 B10. White finish.

**Finish:** Matte white RAL 9010**Weight:** 650 g**Installation:** Suspended**TECHNICAL SPECIFICATIONS:**

|                      |                          |                      |                  |
|----------------------|--------------------------|----------------------|------------------|
| <b>Light output:</b> | 763 lm                   | <b>°K :</b>          | 2700             |
| <b>Plum:</b>         | 10,3W                    | <b>CRI :</b>         | 90               |
| <b>Efficacy:</b>     | 74,1 lm/w                | <b>R9 :</b>          | 61               |
| <b>Type:</b>         | COB                      | <b>MacAdam:</b>      | 3                |
| <b>LED Lifetime:</b> | 72.000 L80 B10 (Ta=25°C) | <b>Power Supply:</b> | 220-240V 50/60Hz |
| <b>Power:</b>        | 8,4W                     | <b>Gear:</b>         | Adjustable DALI  |

**Light output tolerance +/- 10%****CUSTOM MADE OPTIONS:**

K71ST1540OP927DWW

KOMBIC 70 SUT 1500 IP40 9VWW OP D W/W

**PHOTOMETRIC DATA :**

