

KOMBIC 70 SUT

K71ST1540OP930DWW



KOMBIC 70 SUT 1500 IP40 9WW OP D W/W

Description:

LAMP Suspended or ceiling mounting downlight KOMBIC 70 SUT 1500. Body made of recycled aluminium extrusion at a rate of 75% and reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Inner reflector finished in white and opal optical film. Heatsink made of die-cast aluminium. COB LED, colour temperature 3000K and IRC90. Electronic DALI gear included. IP40 rated. Insulation Class II. Photobiological safety group 0. LED life time: 72.000 L80 B10. White finish.

Finish: Matte white RAL 9010

Weight: 650 g

Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output:	796 lm	°K :	3000
Plum:	10,3W	CRI :	90
Efficacy:	77,3 lm/w	R9 :	54
Type:	COB	MacAdam:	3
LED Lifetime:	72.000 L80 B10 (Ta=25°C)	Power Supply:	220-240V 50/60Hz
Power:	8,4W	Gear:	Adjustable DALI

Light output tolerance +/- 10%


CUSTOM MADE OPTIONS:



K71ST1540OP930DWW

KOMBIC 70 SUT 1500 IP40 9WW OP D W/W

PHOTOMETRIC DATA :

