


## KOMBIC 70 SUT

K71ST1540OP940DWW



## KOMBIC 70 SUT 1500 IP40 9NW OP D W/W

**Description:**

LAMP Suspended or ceiling mounting downlight KOMBIC 70 SUT 1500. Body made of recycled aluminium extrusion at a rate of 75% and reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Inner reflector finished in white and opal optical film. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K and IRC90. Electronic DALI gear included. IP40 rated. Insulation Class II. Photobiological safety group 0. LED life time: 72.000 L80 B10. White finish.

**Finish:** Matte white RAL 9010**Weight:** 650 g**Installation:** Suspended**TECHNICAL SPECIFICATIONS:**

<b>Light output:</b>	849 lm	<b>°K :</b>	4000
<b>Plum:</b>	10,3W	<b>CRI :</b>	90
<b>Efficacy:</b>	82,4 lm/w	<b>R9 :</b>	71
<b>Type:</b>	COB	<b>MacAdam:</b>	3
<b>LED Lifetime:</b>	72.000 L80 B10 (Ta=25°C)	<b>Power Supply:</b>	220-240V 50/60Hz
<b>Power:</b>	8,4W	<b>Gear:</b>	Adjustable DALI

**Light output tolerance +/- 10%****CUSTOM MADE OPTIONS:**

K71ST1540OP940DWW

KOMBIC 70 SUT 1500 IP40 9NW OP D W/W

**PHOTOMETRIC DATA :**

