


KOMBIC 70 TRACK

K71TK1520RF927D66



KOMBIC 70 TK 1500 IP20 927 RF FL D SER

Description:

Downlight for mounting on three-phase track model KOMBIC 70 TK 1500. Body made of recycled aluminum extrusion with a rate of 75% and reflector made of recycled polycarbonate R-PC FR WHITE TM with bromine-free flame retardant. Flammability grade V0 according to UL94. Flood reflector for greater efficiency and control of light distribution and lower glare UGR<16. Heat sink made of aluminum injection. LED COB, with color temperature 2700K with CRI90. DALI electronic equipment included. With an IP20 protection rating. Insulation class II. Photobiological safety group 0. Lifespan: 72,000 L80 B10. Available finish SERENA palette (Arena, Bronze, Champagne, Dark Chocolate, Dark Grey, Terracotta). Tolerance of luminous flux $\pm 4\%$ according to finish.

Weight: 600 g**Installation:** 3-Circuit track**TECHNICAL SPECIFICATIONS:**

Plum:	10,3W	°K :	2700
UGR:	19	CRI :	90
Type:	COB	MacAdam:	3
LED Lifetime:	72.000 L80 B10 (Ta=25°C)	Power Supply:	220-240V 50/60Hz
		Gear:	Adjustable DALI

**CUSTOM MADE OPTIONS:**