

KOMBIC 70 TRACK

K71TK1520RF930NWW




KOMBIC 70 TK 1500 IP20 9WW RF FL W/W

Description:

LAMP Suspended or ceiling mounting downlight KOMBIC 70 TK 1500. Body made of recycled aluminium extrusion at a rate of 75% and reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Inner reflector finished in white and Flood reflector for greater efficiency and to achieve controlled light distribution and low glare level, less than UGR<19. Heatsink made of die-cast aluminium. COB LED, colour temperature 3000K and IRC90. Electronic ON OFF gear included. IP20 rated. Insulation Class II. Photobiological safety group 0. LED life time: 72.000 L80 B10. Available finishes: White and black.

Finish: Matte white RAL 9010**Weight:** 560 g**Installation:** 3-Circuit track**TECHNICAL SPECIFICATIONS:**

Light output:	1.000 lm	°K :	3000
Plum:	10,5W	CRI :	90
Efficacy:	95,2 lm/w	R9 :	54
UGR:	19	MacAdam:	3
Type:	COB	Power Supply:	220-240V 50/60Hz
LED Lifetime:	72.000 L80 B10 (Ta=25°C)	Gear:	Electronic
Power:	8,4W		

Light output tolerance +/- 10%**CUSTOM MADE OPTIONS:**

K71TK1520RF930NWW **KOMBIC 70 TK 1500 IP20 9WW RF FL W/W**

PHOTOMETRIC DATA :

