

## KOMBIC 70 TRACK

K71TK1540OP927D66



## KOMBIC 70 TK 1500 IP40 927 OPAL D SER

**Description:**

Downlight for mounting on three-phase track model KOMBIC 70 TK 1500. Body made of recycled aluminum extrusion with a rate of 75% and reflector made of recycled polycarbonate R-PC FR WHITE TM with bromine-free flame retardant. Flammability grade V0 according to UL94. Opal optical film. Heat sink made of aluminum injection. LED COB, with color temperature 2700K with CRI90. DALI electronic equipment included. With a protection degree of IP40. Insulation class II. Photobiological safety group 0. Lifespan: 72,000 L80 B10. Available finish SERENA palette (Arena, Bronze, Champagne, Dark Chocolate, Dark Grey, Terracotta). Tolerance of luminous flux  $\pm 7\%$  according to finish.

**Weight:** 600 g**Installation:** 3-Circuit track**TECHNICAL SPECIFICATIONS:**

|                      |                          |                      |                  |
|----------------------|--------------------------|----------------------|------------------|
| <b>Plum:</b>         | 10,3W                    | <b>°K :</b>          | 2700             |
| <b>Type:</b>         | COB                      | <b>CRI :</b>         | 90               |
| <b>LED Lifetime:</b> | 72.000 L80 B10 (Ta=25°C) | <b>MacAdam:</b>      | 3                |
|                      |                          | <b>Power Supply:</b> | 220-240V 50/60Hz |
|                      |                          | <b>Gear:</b>         | Adjustable DALI  |

**CUSTOM MADE OPTIONS:**