


KOMBIC 70 TRACK

K71TK1540OP940NWW



KOMBIC 70 TK 1500 IP40 9NW OP W/W

Description:

LAMP Suspended or ceiling mounting downlight KOMBIC 70 TK 1500. Body made of recycled aluminium extrusion at a rate of 75% and reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Inner reflector finished in white and opal optical film. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K and IRC90. Electronic ON OFF gear included. IP40 rated. Insulation Class II. Photobiological safety group 0. LED life time: 72.000 L80 B10. White finish.

Finish: Matte white RAL 9010**Weight:** 560 g**Installation:** 3-Circuit track**TECHNICAL SPECIFICATIONS:**

Light output:	849 lm	°K :	4000
Plum:	10,5W	CRI :	90
Efficacy:	80,8 lm/w	R9 :	71
Type:	COB	MacAdam:	3
LED Lifetime:	72.000 L80 B10 (Ta=25°C)	Power Supply:	220-240V 50/60Hz
Power:	8,4W	Gear:	Electronic

Light output tolerance +/- 10%**CUSTOM MADE OPTIONS:**

K71TK1540OP940NWW

KOMBIC 70 TK 1500 IP40 9NW OP W/W

PHOTOMETRIC DATA :

