


## KOMBIC 70 TRACK

K71TK1540WF830N66



## KOMBIC 70 TK 1500 IP40 830 WFL SER

**Description:**

Downlight for mounting on three-phase track model KOMBIC 70 TK 1500. Body made of recycled aluminum extrusion with a rate of 75% and reflector made of recycled polycarbonate R-PC FR WHITE TM with bromine-free flame retardant. Flammability grade V0 according to UL94. Wide flood optics with control of light distribution and low glare UGR<16. Heat sink made of aluminum injection. LED COB, with color temperature 3000K with CRI80. ON OFF electronic equipment included. With a protection degree of IP40. Insulation class II. Photobiological safety group 0. Lifespan: 72,000 L80 B10. Available finish SERENA palette (Arena, Bronze, Champagne, Dark Chocolate, Dark Grey, Terracotta). Tolerance of luminous flux  $\pm 5\%$  according to finish.

**Weight:** 580 g**Installation:** 3-Circuit track**TECHNICAL SPECIFICATIONS:**

|                      |                          |                      |                  |
|----------------------|--------------------------|----------------------|------------------|
| <b>Plum:</b>         | 10,5W                    | <b>°K :</b>          | 3000             |
| <b>UGR:</b>          | 19                       | <b>CRI :</b>         | 80               |
| <b>Type:</b>         | COB                      | <b>MacAdam:</b>      | 3                |
| <b>LED Lifetime:</b> | 72.000 L80 B10 (Ta=25°C) | <b>Power Supply:</b> | 220-240V 50/60Hz |
|                      |                          | <b>Gear:</b>         | Electronic       |

**CUSTOM MADE OPTIONS:**