

KOMBIC 70 TRACK

K71TK1540WF930D66



KOMBIC 70 TK 1500 IP40 930 WFL D SER

Description:

Downlight for mounting on three-phase track model KOMBIC 70 TK 1500. Body made of recycled aluminum extrusion with a rate of 75% and reflector made of recycled polycarbonate R-PC FR WHITE TM with bromine-free flame retardant. Flammability grade V0 according to UL94. Wide flood optics with control of light distribution and low glare UGR<16. Heat sink made of aluminum injection. LED COB, with color temperature 3000K with CRI90. DALI electronic equipment included. With a protection degree of IP40. Insulation class II. Photobiological safety group 0. Lifespan: 72,000 L80 B10. Available finish SERENA palette (Arena, Bronze, Champagne, Dark Chocolate, Dark Grey, Terracotta). Tolerance of luminous flux $\pm 5\%$ according to finish.

Weight: 620 g**Installation:** 3-Circuit track**TECHNICAL SPECIFICATIONS:**

Light output:	964 lm	°K :	3000
Plum:	10W	CRI :	90
Efficacy:	96,4 lm/w	R9 :	66
UGR:	<19	MacAdam:	3
Type:	COB	Power Supply:	220-240V 50/60Hz
LED Lifetime:	100.000h L90 B10 (Ta=25°C)	Gear:	Adjustable DALI
Power:	8,4W		

Light output tolerance $\pm 10\%$ **CUSTOM MADE OPTIONS:**

K71TK1540WF930D66 **KOMBIC 70 TK 1500 IP40 930 WFL D SER**

PHOTOMETRIC DATA :

