KOMBIC 70 TRACK


K71TS1520RF827DWW



KOMBIC 70 TS 1500 IP20 VWW RF FL D W/W

Description:

Downlight to attach to three-phase track model KOMBIC 70 TS 1500 from the LAMP brand. Body made of recycled aluminum extrusion with a rate of 75% and R-PC FR WHITE TM recycled polycarbonate reflector with bromine-free flame retardant. Flammability grade V0 according to UL94. Interior reflector finished in white color. Flood reflector for greater efficiency and control of light distribution and lower glare UGR<19. Heatsink made of aluminum injection. COB LED, with 2700K color temperature with CRI80. DALI electronic equipment included. With an IP20 protection degree. Insulation class II. Photobiological safety group 0. LED life time: 72,000 L80 B10. Finished in black and white.



Finish: Matte white RAL 9010

Weight: 600 g

Installation: 3-Circuit track

TECHNICAL SPECIFICATIONS:

Light output: 1.120 lm °K: 2700 Plum: 10,5W CRI: 80 Efficacy: 108,8 lm/w 3 MacAdam:

UGR: 19 Power Supply: 220-240V 50/60Hz Type: СОВ Gear: Adjustable DALI

LED Lifetime: 72.000 L80 B10 (Ta=25°C)

8,4W Power:

Light output tolerance +/- 10%































CUSTOM MADE OPTIONS:















KOMBIC 70 TRACK



K71TS1520RF827DWW


KOMBIC 70 TS 1500 IP20 VWW RF FL D W/W


PHOTOMETRIC DATA:


 $\label{eq:control_equation} \begin{aligned} & \mathsf{K71TS1520RF827DWW} \\ & \eta = \mathsf{100\%} \end{aligned}$

Imax = 2307 cd/klm UTE: 1,00A

CIE: 92 98 100 100 100







Data according to regulations 2019/2020/EU and 2019/2015/EU