


KOMBIC 70 TRACK

K71TS1520RW827D66



KOMBIC 70 TS 1500 IP20 827 RF WFL D SER

Description:

Downlight to be mounted on a three-phase track model KOMBIC 70 TS 1500. Body made of recycled aluminum extrusion with a rate of 75% and reflector made of recycled polycarbonate R-PC FR WHITE TM with bromine-free flame retardant. Flammability grade V0 according to UL94. Heat sink made of aluminum injection. LED COB, with color temperature 2700K with CRI80. DALI electronic equipment included. With an IP20 protection rating. Insulation class II. Photobiological safety group 0. Lifespan: 72,000 L80 B10. Available finish SERENA palette (Arena, Bronze, Champagne, Dark Chocolate, Dark Grey, Terracotta). Tolerance of luminous flux $\pm 4\%$ according to finish.

Weight: 600 g**Installation:** 3-Circuit track**TECHNICAL SPECIFICATIONS:**

Plum:	10,5W	°K :	2700
UGR:	19	CRI :	80
Type:	COB	MacAdam:	3
LED Lifetime:	72.000 L80 B10 (Ta=25°C)	Power Supply:	220-240V 50/60Hz
Power:	8,4W	Gear:	Adjustable DALI

**CUSTOM MADE OPTIONS:**