


## KOMBIC 70 TRACK

K71TS1520RW930D66



## KOMBIC 70 TS 1500 IP20 930 RF WFL D SER

**Description:**

Downlight to be mounted on a three-phase track model KOMBIC 70 TS 1500. Body made of recycled aluminum extrusion with a rate of 75% and reflector made of recycled polycarbonate R-PC FR WHITE TM with bromine-free flame retardant. Flammability grade V0 according to UL94. Heat sink made of aluminum injection. LED COB, with color temperature 3000K with CRI90. DALI electronic equipment included. With a protection degree of IP20. Insulation class II. Photobiological safety group 0. Lifespan: 72,000 L80 B10. Available finish SERENA palette (Arena, Bronze, Champagne, Dark Chocolate, Dark Grey, Terracotta). Tolerance of luminous flux  $\pm 4\%$  according to finish.

**Weight:** 600 g**Installation:** 3-Circuit track**TECHNICAL SPECIFICATIONS:**

<b>Plum:</b>	10,5W	<b>°K :</b>	3000
<b>UGR:</b>	19	<b>CRI :</b>	90
<b>Type:</b>	COB	<b>MacAdam:</b>	3
<b>LED Lifetime:</b>	72.000 L80 B10 (Ta=25°C)	<b>Power Supply:</b>	220-240V 50/60Hz
<b>Power:</b>	8,4W	<b>Gear:</b>	Adjustable DALI

**CUSTOM MADE OPTIONS:**