KOMBIC 70 TRACK


K71TS1540OP827DWW



KOMBIC 70 TS 1500 IP40 VWW OP D W/W

Description:

Downlight to attach to three-phase track model KOMBIC 70 TS 1500 from the LAMP brand. Body made of recycled aluminum extrusion with a rate of 75% and R-PC FR WHITE TM recycled polycarbonate reflector with bromine-free flame retardant. Flammability grade V0 according to UL94. Interior reflector finished in white color. Opal optical sheet. Heatsink made of aluminum injection. COB LED, with 2700K color temperature with CRI80. DALI electronic equipment included. With an IP40 protection degree. Insulation class II. Photobiological safety group 0. LED life time: 72,000 L80 B10. Finished in white.



Finish: Matte white RAL 9010

Weight: 600 g

Installation: 3-Circuit track

TECHNICAL SPECIFICATIONS:

Light output: 892 lm °K: 2700 Plum: 10,5W CRI: 80 Efficacy: 86,6 lm/w 3 MacAdam:

Type: СОВ Power Supply: 220-240V 50/60Hz LED Lifetime: 72.000 L80 B10 (Ta=25°C) Gear: Adjustable DALI

Power: 8,4W

Light output tolerance +/- 10%























CUSTOM MADE OPTIONS:















KOMBIC 70 TRACK



K71TS1540OP827DWW

KOMBIC 70 TS 1500 IP40 VWW OP D W/W

PHOTOMETRIC DATA:

K71TS1540OP827DWW η = 100% lmax = 1458 cd/klmUTE: 1,00A

CIE: 92 97 100 100 100

