


KOMBIC 70 TRACK

K71TS1540OP830D66



KOMBIC 70 TS 1500 IP40 830 OPAL D SER

Description:

Downlight to be mounted on a three-phase track model KOMBIC 70 TS 1500. Body made of recycled aluminum extrusion with a rate of 75% and reflector made of recycled polycarbonate R-PC FR WHITE TM with bromine-free flame retardant. Flammability grade V0 according to UL94. Opal optical film. Heat sink made of aluminum injection. LED COB, with color temperature 3000K with CRI80. DALI electronic equipment included. With an IP40 protection rating. Insulation class II. Photobiological safety group 0. Lifespan: 72,000 L80 B10. Available finish SERENA palette (Arena, Bronze, Champagne, Dark Chocolate, Dark Grey, Terracotta). Tolerance of luminous flux $\pm 7\%$ according to finish.

Weight: 600 g

Installation: 3-Circuit track

TECHNICAL SPECIFICATIONS:

Plum:	10,5W	°K :	3000
Type:	COB	CRI :	80
LED Lifetime:	72.000 L80 B10 (Ta=25°C)	MacAdam:	3
Power:	8,4W	Power Supply:	220-240V 50/60Hz
		Gear:	Adjustable DALI



CUSTOM MADE OPTIONS:

