


KOMBIC 70 TRACK

K71TS1540OP840DWW




KOMBIC 70 TS 1500 IP40 NW OP D W/W

Description:

Downlight to attach to three-phase track model KOMBIC 70 TS 1500 from the LAMP brand. Body made of recycled aluminum extrusion with a rate of 75% and R-PC FR WHITE TM recycled polycarbonate reflector with bromine-free flame retardant. Flammability grade V0 according to UL94. Interior reflector finished in white color Opal optical sheet Heatsink made of aluminum injection. COB LED, with 4000K color temperature with CRI80. DALI electronic equipment included. With an IP40 protection degree. Insulation class II. Photobiological safety group 0. LED life time: 72,000 L80 B10. Finished in white.

Finish: Matte white RAL 9010**Weight:** 600 g**Installation:** 3-Circuit track**TECHNICAL SPECIFICATIONS:**

Light output:	981 lm	°K :	4000
Plum:	10,5W	CRI :	80
Efficacy:	95,2 lm/w	MacAdam:	3
Type:	COB	Power Supply:	220-240V 50/60Hz
LED Lifetime:	72.000 L80 B10 (Ta=25°C)	Gear:	Adjustable DALI
Power:	8,4W		

Light output tolerance +/- 10%**CUSTOM MADE OPTIONS:**

K71TS1540OP840DWW

KOMBIC 70 TS 1500 IP40 NW OP D W/W

PHOTOMETRIC DATA :

