## LAMPTUB 60 SUSP. CEILING ROSE



### L61SE084LOIO940NW

LTUB60 SU RE 840 2400 NW D/I OP WH



### Description:

Surface mounted luminaire Lamptub 60 from LAMP. Made of recycled aluminium extrusion with circular section of 60mm and length of 840mm. Direct-indirect light model with opal polycarbonate diffuser. Model for MID-POWER LED, with colour temperature 4000K with CRI90. Built-in electronic ON/OFF control gear. With IP40, IK07 degree of protection. Insulation class I / II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.



Finish: Matte white RAL 9010

Installation: Suspended

### **TECHNICAL SPECIFICATIONS:**

Light output: 1.430 lm °K: 4000 Plum: 17,4W CRI: 90 Efficacy: 82,1 lm/w 70 R9: Type: MID POWER LED MacAdam: 3

LED Lifetime: 72.000 L80 B10 (Ta=25°C) Power Supply: 220-240V 50/60Hz

Gear: Power: 15.1W Electronic

# Light output tolerance +/- 10%









































**CUSTOM MADE OPTIONS:** 



















## LAMPTUB 60 SUSP. CEILING ROSE





L61SE084LOIO940NW


## LTUB60 SU RE 840 2400 NW D/I OP WH


## **PHOTOMETRIC DATA:**

L61SE084LOIO940NW η = 100% Imax = 213 cd/klm UTE: 0,55E + 0,46T CIE: 50 81 97 54 100
















## LAMPTUB 60 SUSP. CEILING ROSE



# ACCESORIES:

## Assembly



Product code:

L6SUECB



LTUB60 ACC. SUR END COVER BK.



Product code:

L6SUECW

Description:

LTUB60 ACC. SUR END COVER WH.



Product code:

L6SUECW3

Description:

LTUB60 ACC. SUR END COVER WE.



Product code:

L6SUECW4

Description:

LTUB60 ACC. SUR END COVER BS.