LAMPTUB 60 SUSP. CEILING ROSE



L61SE084MOIO927NW




LTUB60 SU RE 840 3500 VWW D/I OP WH

Description:

Surface mounted luminaire Lamptub 60 from LAMP. Made of recycled aluminium extrusion with circular section of 60mm and length of 840mm. Direct-indirect light model with opal polycarbonate diffuser. Model for MID-POWER LED, with colour temperature 2700K with CRI90. Built-in electronic ON/OFF control gear. With IP40, IK07 degree of protection. Insulation class I / II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.

Finish: Matte white RAL 9010



Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output: 2.068 Im °K: 2700 Plum: 25,9W CRI: 90 Efficacy: 79,8 lm/w R9: 57 Type: MID POWER LED MacAdam: 3

LED Lifetime: 72.000 L80 B10 (Ta=25°C) Power Supply: 220-240V 50/60Hz

Gear: Power: 27.7W Electronic

Light output tolerance +/- 10%



























CUSTOM MADE OPTIONS:

RAW

LAMPTUB 60 SUSP. CEILING ROSE





L61SE084MOIO927NW


LTUB60 SU RE 840 3500 VWW D/I OP WH


PHOTOMETRIC DATA:


L61SE084MOIO927NW η = 100% lmax = 277 cd/klmUTE: 0,71E + 0,29T CIE: 50 81 97 71 100

















LAMPTUB 60 SUSP. CEILING ROSE



ACCESORIES:

Assembly



Product code:

L6SUECB



LTUB60 ACC. SUR END COVER BK.



Product code:

L6SUECW



LTUB60 ACC. SUR END COVER WH.



Product code:

L6SUECW3

Description:

LTUB60 ACC. SUR END COVER WE.



Product code:

L6SUECW4

Description:

LTUB60 ACC. SUR END COVER BS.