LAMPTUB 60 SUSP. CEILING ROSE

**LAMP**
Worktitude for light

L61SE084MOIO940NW   **-**   **LTUB60 SU RE 840 3700 NW D/I OPAL WH**

Description:

Surface mounted luminaire Lamptub 60 from LAMP. Made of recycled aluminium extrusion with circular section of 60mm and length of 840mm. Direct-indirect light model with opal polycarbonate diffuser. Model for MID-POWER LED, with colour temperature 4000K with CRI90. Built-in electronic ON/OFF control gear. With IP40, IK07 degree of protection. Insulation class I / II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.

Finish: Matte white RAL 9010

63

Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output:	2.246 lm		**ºK :**	4000
Plum:	25,9W		**CRI :**	90
Efficacy:	86,7 lm/w		**R9 :**	70
Type:	MID POWER LED		**MacAdam:**	3
LED Lifetime:	72.000 L80 B10 (Ta=25ºC)		**Power Supply:**	220-240V 50/60Hz
Power:	27.7W		**Gear:**	Electronic

Light output tolerance +/- 10%

LED
4000ºK

30mm

CUSTOM MADE OPTIONS:

RAW

15-05-2025

LAMPTUB 60 SUSP. CEILING ROSE

LAMP
Worktitude for light

**L61SE084MOIO940NW**   LTUB60 SU RE 840 3700 NW D/I OPAL WH

PHOTOMETRIC DATA :

L61SE084MOIO940NW

η = 100%

Imax = 277 cd/klm

UTE: 0,71E + 0,29T

CIE: 50 81 97 71 100

alpha = 102,2º

BACK   FRONT

35,6 %   35,6 %

Melanopic Lux Ratio: 0.557

Rf 90.5 - Rg 100.4

1 - Limits on the Planckian locus

2 - Limits for practical sources

15-05-2025

Data according to regulations 2019/2020/EU and 2019/2015/EU

LAMPTUB 60 SUSP. CEILING ROSE

LAMP
Worktitude for light

ACCESORIES :

Assembly

Product code:	**Description:**
L6SUECB	LTUB60 ACC. SUR END COVER BK.

Product code:	**Description:**
L6SUECW	LTUB60 ACC. SUR END COVER WH.

Product code:	**Description:**
L6SUECW3	LTUB60 ACC. SUR END COVER WE.

Product code:	**Description:**
L6SUECW4	LTUB60 ACC. SUR END COVER BS.