# LAMPTUB 60 SUSP. CEILING ROSE


### L61SE084MOOC940NW

#### LTUB60 SU RE 840 2600 NW COMF WH

### Description:

Surface mounted luminaire Lamptub 60 from LAMP. Made of recycled aluminium extrusion with circular section of 60mm and length of 840mm, an opal comfort diffuser made of a translucent polycarbonate diffuser and an optical film to achieve a controlled light distribution and low UGR<19. Model for MID-POWER LED, with colour temperature 4000K with CRI90. Built-in electronic ON/OFF control gear. With IP40, IK07 degree of protection. Insulation class I / II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.

Finish: Matte white RAL 9010



Installation: Suspended

#### **TECHNICAL SPECIFICATIONS:**

Light output:	1.476 lm	°K :	4000
Plum:	17,8W	CRI :	90
Efficacy:	82,9 lm/w	R9 :	70
UGR:	<19	MacAdam:	3
Туре:	MID POWER LED	Power Supply:	220-240V 50/60Hz
LED Lifetime:	72.000 L80 B10 (Ta=25ºC)	Gear:	Electronic
Power:	15.1W		

#### Light output tolerance +/- 10%



**CUSTOM MADE OPTIONS:** 




Worktitude for light


## LAMPTUB 60 SUSP. CEILING ROSE

L61SE084MOOC940NW

LTUB60 SU RE 840 2600 NW COMF WH







LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es

Worktitude for light

# LAMPTUB 60 SUSP. CEILING ROSE

## ACCESORIES :

### Assembly



Product code: L6SUECB

Description: LTUB60 ACC. SUR END COVER BK.



Product code: L6SUECW

Description: LTUB60 ACC. SUR END COVER WH.



Product code: L6SUECW3

Description: LTUB60 ACC. SUR END COVER WE.



Product code: L6SUECW4

Description: LTUB60 ACC. SUR END COVER BS.