Product datasheet

LAMPTUB 60 SUSP. CEILING ROSE

L61SE084MOTE930NW

LTUB60 SU RE 840 2200 9WW TECH WH

Description:

Surface-mounted luminaire, model LAMPTUB 60 TECH by LAMP. Made of 80% recycled aluminium extrusion, with circular section of 60mm and length 840 mm, with matt black reflector ULTRA COMFORT and optics for light distribution control and low glare UGR<16. Model for MID-POWER LED, with colour temperature 3000K and CRI90. Built-in electronic wiring. With IP20, IK07 degree of protection. Insulation class I/II. Photobiological safety group 0. Lifetime:50000 L90 B10 Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.



Finish: Matte white RAL 9010

Dimensions: 840 x 67 x 80 mm

Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output:	1.260 lm	**ºK :**	3000
Plum:	13,7W	**CRI :**	90
Efficacy:	92 lm/w	**R9 :**	61
UGR:	<16	**MacAdam:**	3
Type:	MID POWER LED	**Power Supply:**	220-240V 50/60Hz
LED Lifetime:	50.000 L90 B10 (Ta=25ºC)	**Gear:**	Electronic
Power:	11W		

Light output tolerance +/- 10%

CUSTOM MADE OPTIONS:

LAMPTUB 60 SUSP. CEILING ROSE

L61SE084MOTE930NW **LTUB60 SU RE 840 2200 9WW TECH WH**

PHOTOMETRIC DATA :

L61SE084MOTE930NW

η = 100%

Imax = 1305 cd/klm

UTE:

CIE: 98 100 100 100 100











Melanopic Lux Ratio: 0.554







LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es

Data according to regulations 2019/2020/EU and 2019/2015/EU

LAMPTUB 60 SUSP. CEILING ROSE

ACCESORIES :

Assembly

Product code:	Description:
L6SUECB	LTUB60 ACC. SUR END COVER BK.

Product code:	Description:
L6SUECW	LTUB60 ACC. SUR END COVER WH.

Product code:	Description:
L6SUECW3	LTUB60 ACC. SUR END COVER WE.

Product code:	Description:
L6SUECW4	LTUB60 ACC. SUR END COVER BS.