LAMPTUB 60 SUSP. CEILING ROSE

L61SE084MOTE940NB

LTUB60 SU RE 840 2200 9NW TECH BK

Matte black RAL 9011

840 x 67 x 80 mm

THE REPORT OF TH

Description:

Finish:

Dimensions:

""""""Surface-mounted luminaire, model LAMPTUB 60 TECH by LAMP. Made of 80% recycled aluminium extrusion, with circular section of 60mm and length 840 mm, with matt black reflector ULTRA COMFORT and optics for light distribution control and low glare UGR<16. Model for MID-POWER LED, with colour temperature 4000K and CRI90. Built-in electronic wiring. With IP20, IK07 degree of protection. Insulation class I/II. Photobiological safety group 0. Lifetime:50000 L90 B10 Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.""" "



Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output:	1.320 lm	⁰K :	4000
Plum:	13,7W	CRI :	90
Efficacy:	96,4 lm/w	R9 :	85
UGR:	<16	MacAdam:	3
Туре:	MID POWER LED	Power Supply:	220-240V 50/60Hz
LED Lifetime:	50.000 L90 B10 (Ta=25⁰C)	Gear:	Electronic
Power:	11W		

Light output tolerance +/- 10%

CUSTOM MADE OPTIONS:




Worktitude for light


LAMPTUB 60 SUSP. CEILING ROSE

L61SE084MOTE940NB

LTUB60 SU RE 840 2200 9NW TECH BK







Worktitude for light

LAMPTUB 60 SUSP. CEILING ROSE

ACCESORIES :

Assembly



Product code: L6SUECB

Description: LTUB60 ACC. SUR END COVER BK.



Product code: L6SUECW

Description: LTUB60 ACC. SUR END COVER WH.

Worktitude for light



Product code: L6SUECW3

Description: LTUB60 ACC. SUR END COVER WE. Product code:

L6SUECW4

Description: LTUB60 ACC. SUR END COVER BS.