LAMPTUB 60 SUSP. CEILING ROSE



L61SE112LOIO940N4




LTUB60 SU RE 1120 3300 NW D/I OP BS

Description:

Surface mounted luminaire Lamptub 60 from LAMP. Made of recycled aluminium extrusion with circular section of 60mm and length of 1120mm. Direct-indirect light model with opal polycarbonate diffuser. Model for MID-POWER LED, with colour temperature 4000K with CRI90. Built-in electronic ON/OFF control gear. With IP40, IK07 degree of protection. Insulation class I / II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.

Finish: Palette BE SOCIAL - 4 TEXTURED



Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output: 1.950 lm °K: 4000 Plum: 22,6W CRI: 90 Efficacy: 86,2 lm/w 70 R9: Type: MID POWER LED MacAdam: 3

LED Lifetime: 72.000 L80 B10 (Ta=25°C) Power Supply: 220-240V 50/60Hz

Gear: Power: 21.6W Electronic

Light output tolerance +/- 10%





CUSTOM MADE OPTIONS:



LAMPTUB 60 SUSP. CEILING ROSE





L61SE112LOIO940N4


LTUB60 SU RE 1120 3300 NW D/I OP BS


PHOTOMETRIC DATA:


L61SE112LOIO940N4 η = 100% Imax = 208 cd/klm UTE: 0,53E + 0,47T CIE: 50 81 98 53 100















LAMPTUB 60 SUSP. CEILING ROSE



ACCESORIES:

Assembly



Product code:

L6SUECB



LTUB60 ACC. SUR END COVER BK.



Product code:

L6SUECW



LTUB60 ACC. SUR END COVER WH.



Product code:

L6SUECW3

Description:

LTUB60 ACC. SUR END COVER WE.



Product code:

L6SUECW4

Description:

LTUB60 ACC. SUR END COVER BS.