#### LAMPTUB 60 SUSP. CEILING ROSE



#### L61SE112LOIP940DW




## - LTUB60 SU RE 1120 3300 NW D/I COMF DA WH

#### Description:

Surface mounted luminaire Lamptub 60 from LAMP. Made of recycled aluminium extrusion with circular section of 60mm and length of 1120mm. Direct-indirect light model with opal comfort diffuser made of a translucent polycarbonate diffuser and an optical film to achieve a controlled light distribution and low UGR<16. Model for MID-POWER LED, with colour temperature 4000K with CRI90. Built-in electronic DALI control gear. With IP40, IK07 degree of protection. Insulation class I / II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.

Finish: Matte white RAL 9010



Installation: Suspended

#### **TECHNICAL SPECIFICATIONS:**

 Light output:
 1.872 lm
 °K:
 4000

 Plum:
 22,6W
 CRI:
 90

 Efficacy:
 82,8 lm/w
 R9:
 70

 UGR:
 <16</td>
 MacAdam:
 3

 Type:
 MID POWER LED
 Power Supply:
 220-240V 50/60Hz

 LED Lifetime:
 72.000 L80 B10 (Ta=25°C)
 Gear:
 Adjustable DALI

**Power:** 21.6W

## Light output tolerance +/- 10%

























## **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU












### LAMPTUB 60 SUSP. CEILING ROSE





L61SE112LOIP940DW


## LTUB60 SU RE 1120 3300 NW D/I COMF DA WH


#### **PHOTOMETRIC DATA:**



















## LAMPTUB 60 SUSP. CEILING ROSE



# ACCESORIES:

### **Assembly**



Product code:

L6SUECB



LTUB60 ACC. SUR END COVER BK.



Product code:

L6SUECW



LTUB60 ACC. SUR END COVER WH.



Product code:

L6SUECW3

Description:

LTUB60 ACC. SUR END COVER WE.



Product code:

L6SUECW4

Description:

LTUB60 ACC. SUR END COVER BS.