## LAMPTUB 60 SUSP. CEILING ROSE



## L61SE112LOOP927NW

LTUB60 SU RE 1120 1700 VWW OPAL WH



## Description:

Surface mounted luminaire Lamptub 60 from LAMP. Made of recycled aluminium extrusion with circular section of 60mm and length of 1120mm, with opal polycarbonate diffuser. Model for MID-POWER LED, with colour temperature 2700K with CRI90. Built-in electronic ON/OFF control gear. With IP40, IK07 degree of protection. Insulation class I / II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.



Finish: Matte white RAL 9010

Installation: Suspended

## **TECHNICAL SPECIFICATIONS:**

Light output: 955 lm °K: 2700 Plum: 12,9W CRI: 90 Efficacy: 74 lm/w R9: 57 Type: MID POWER LED MacAdam: 3

LED Lifetime: 72.000 L80 B10 (Ta=25°C) Power Supply: 220-240V 50/60Hz

Gear: Power: 10.6W Electronic

## Light output tolerance +/- 10%





























## **CUSTOM MADE OPTIONS:**





















## LAMPTUB 60 SUSP. CEILING ROSE





L61SE112LOOP927NW


## **LTUB60 SU RE 1120 1700 VWW OPAL WH**


## **PHOTOMETRIC DATA:**


L61SE112LOOP927NW  $\eta$  = 100% lmax = 390 cd/klmUTE: 1,00E + 0,00T CIE: 50 81 97 100 100
















## LAMPTUB 60 SUSP. CEILING ROSE



# ACCESORIES:

# Assembly



Product code:

L6SUECB



LTUB60 ACC. SUR END COVER BK.



Product code:

L6SUECW

Description:

LTUB60 ACC. SUR END COVER WH.



Product code:

L6SUECW3

Description:

LTUB60 ACC. SUR END COVER WE.



Product code:

L6SUECW4

Description:

LTUB60 ACC. SUR END COVER BS.