#### LAMPTUB 60 SUSP. CEILING ROSE



#### L61SE112MOIO927NW


## LTUB60 SU RE 1120 4700 VWW D/I OP WH



#### Description:

Surface mounted luminaire Lamptub 60 from LAMP. Made of recycled aluminium extrusion with circular section of 60mm and length of 1120mm. Direct-indirect light model with opal polycarbonate diffuser. Model for MID-POWER LED, with colour temperature 2700K with CRI90. Built-in electronic ON/OFF control gear. With IP40, IK07 degree of protection. Insulation class I / II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.

Finish: Matte white RAL 9010



#### Installation: Suspended

#### **TECHNICAL SPECIFICATIONS:**

Light output: 2.798 lm °K: 2700 Plum: 35,1W CRI: 90 Efficacy: 79,7 lm/w R9: 57 Type: MID POWER LED MacAdam: 3

LED Lifetime: 72.000 L80 B10 (Ta=25°C) Power Supply: 220-240V 50/60Hz

Gear: Power: 40.5W Electronic

### Light output tolerance +/- 10%



































## **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU













## LAMPTUB 60 SUSP. CEILING ROSE





**L61SE112MOIO927NW** 


## LTUB60 SU RE 1120 4700 VWW D/I OP WH


#### **PHOTOMETRIC DATA:**


L61SE112MOIO927NW  $\eta$  = 100% lmax = 273 cd/klmUTE: 0,70E + 0,30T CIE: 50 81 97 70 100















## LAMPTUB 60 SUSP. CEILING ROSE



# ACCESORIES:

## **Assembly**



Product code:

L6SUECB



LTUB60 ACC. SUR END COVER BK.



Product code:

L6SUECW



LTUB60 ACC. SUR END COVER WH.



Product code:

L6SUECW3

Description:

LTUB60 ACC. SUR END COVER WE.



Product code:

L6SUECW4

Description:

LTUB60 ACC. SUR END COVER BS.