## LAMPTUB 60 SUSP. CEILING ROSE



## L61SE112MOIO940NB




# LTUB60 SU RE 1120 5000 NW D/I OPAL BK

## Description:

Surface mounted luminaire Lamptub 60 from LAMP. Made of recycled aluminium extrusion with circular section of 60mm and length of 1120mm. Direct-indirect light model with opal polycarbonate diffuser. Model for MID-POWER LED, with colour temperature 4000K with CRI90. Built-in electronic ON/OFF control gear. With IP40, IK07 degree of protection. Insulation class I / II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.

Finish: Matte black RAL 9011



#### Installation: Suspended

## **TECHNICAL SPECIFICATIONS:**

Light output: 3.039 Im °K: 4000 Plum: 35,1W CRI: 90 Efficacy: 86,5 lm/w 70 R9: Type: MID POWER LED MacAdam: 3

**LED Lifetime:** 72.000 L80 B10 (Ta=25°C) **Power Supply:** 220-240V 50/60Hz

Power: 40.5W Gear: Electronic

## Light output tolerance +/- 10%

























## **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU













# LAMPTUB 60 SUSP. CEILING ROSE





L61SE112MOIO940NB


# LTUB60 SU RE 1120 5000 NW D/I OPAL BK


## **PHOTOMETRIC DATA:**


L61SE112MOIO940NB  $\eta$  = 100% lmax = 273 cd/klmUTE: 0,70E + 0,30T CIE: 50 81 97 70 100
















# LAMPTUB 60 SUSP. CEILING ROSE



# ACCESORIES:

## **Assembly**



Product code:

L6SUECB



LTUB60 ACC. SUR END COVER BK.



Product code:

L6SUECW



LTUB60 ACC. SUR END COVER WH.



Product code:

L6SUECW3

Description:

LTUB60 ACC. SUR END COVER WE.



Product code:

L6SUECW4

Description:

LTUB60 ACC. SUR END COVER BS.