LAMPTUB 60 SUSP. CEILING ROSE



L61SE112MOIP930N4



LTUB60 SU RE 1120 4800 WW D/I COMF BS

Description:

Surface mounted luminaire Lamptub 60 from LAMP. Made of recycled aluminium extrusion with circular section of 60mm and length of 1120mm. Direct-indirect light model with opal comfort diffuser made of a translucent polycarbonate diffuser and an optical film to achieve a controlled light distribution and low UGR<19. Model for MID-POWER LED, with colour temperature 3000K with CRI90. Built-in electronic ON/OFF control gear. With IP40, IK07 degree of protection. Insulation class I / II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.



Palette BE SOCIAL - 4 TEXTURED Finish:

Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output: 2.790 lm °K: 3000 Plum: 35,1W CRI: 90 Efficacy: 79,4 lm/w 64 R9: UGR: <19 MacAdam: 3

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 72.000 L80 B10 (Ta=25°C) Gear: Electronic

40.5W Power:

Light output tolerance +/- 10%





































CUSTOM MADE OPTIONS:











Data according to regulations 2019/2020/EU and 2019/2015/EU











LAMPTUB 60 SUSP. CEILING ROSE





L61SE112MOIP930N4


LTUB60 SU RE 1120 4800 WW D/I COMF BS


PHOTOMETRIC DATA:


L61SE112MOIP930N4 η = 100% lmax = 453 cd/klmUTE: 0,69C + 0,32T CIE: 66 90 99 68 100















LAMPTUB 60 SUSP. CEILING ROSE



ACCESORIES:

Assembly



Product code:

L6SUECB



LTUB60 ACC. SUR END COVER BK.



Product code:

L6SUECW

Description:

LTUB60 ACC. SUR END COVER WH.



Product code:

L6SUECW3

Description:

LTUB60 ACC. SUR END COVER WE.



Product code:

L6SUECW4

Description:

LTUB60 ACC. SUR END COVER BS.