#### LAMPTUB 60 SUSP. CEILING ROSE



#### L61SE112MOTE930NW



## LTUB60 SU RE 1120 2960 9WW TECH WH

#### Description:

Surface-mounted luminaire, model LAMPTUB 60 TECH by LAMP. Made of 80% recycled aluminium extrusion, with circular section of 60mm and length 1120 mm, with matt black reflector ULTRA COMFORT and optics for light distribution control and low glare UGR<16. Model for MID-POWER LED, with colour temperature 3000K and CRI90. Built-in electronic wiring. With IP20, IK07 degree of protection. Insulation class I/II. Photobiological safety group 0. Lifetime:50000 L90 B10 Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.



Finish: Matte white RAL 9010 1.120 x 67 x 80 mm Dimensions:

Installation: Suspended

#### **TECHNICAL SPECIFICATIONS:**

Light output: 1.680 lm °K: 3000 Plum: 17,8W CRI: 90 Efficacy: 94,4 Im/w 61 R9: UGR: MacAdam: 3

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 50.000 L90 B10 (Ta=25°C) Gear: Electronic

14W Power:

# Light output tolerance +/- 10%



































## **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU











## LAMPTUB 60 SUSP. CEILING ROSE





L61SE112MOTE930NW


## LTUB60 SU RE 1120 2960 9WW TECH WH


### **PHOTOMETRIC DATA:**


L61SE112MOTE930NW  $\eta$  = 100% lmax = 1305 cd/klmUTE: CIE: 98 100 100 100 100




















## LAMPTUB 60 SUSP. CEILING ROSE



# ACCESORIES:

### **Assembly**



Product code:

L6SUECB



LTUB60 ACC. SUR END COVER BK.



Product code:

L6SUECW

Description:

LTUB60 ACC. SUR END COVER WH.



Product code:

L6SUECW3

Description:

LTUB60 ACC. SUR END COVER WE.



Product code:

L6SUECW4

Description:

LTUB60 ACC. SUR END COVER BS.