LAMPTUB 60 SUSP. CEILING ROSE



L61SE168LOOP940DB




LTUB60 SU RE 1680 2700 NW OPAL DALI BK

Description:

Surface mounted luminaire Lamptub 60 from LAMP. Made of recycled aluminium extrusion with circular section of 60mm and length of 1680mm, with opal polycarbonate diffuser. Model for MID-POWER LED, with colour temperature 4000K with CRI90. Built-in electronic DALI control gear. With IP40, IK07 degree of protection. Insulation class I / II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.

Finish: Matte black RAL 9011



Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output: 1.556 lm °K: 4000 Plum: 17,7W CRI: 90 Efficacy: 87,9 lm/w R9: 70 Type: MID POWER LED MacAdam: 3

LED Lifetime: 72.000 L80 B10 (Ta=25°C) Power Supply: 220-240V 50/60Hz Gear: Power: 14.9W Adjustable DALI

Light output tolerance +/- 10%

































CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU













LAMPTUB 60 SUSP. CEILING ROSE





L61SE168LOOP940DB


LTUB60 SU RE 1680 2700 NW OPAL DALI BK


PHOTOMETRIC DATA:


L61SE168LOOP940DB η = 100% Imax = 390 cd/klm UTE: 1,00E + 0,00T CIE: 50 81 97 100 100















LAMPTUB 60 SUSP. CEILING ROSE



ACCESORIES:

Assembly



Product code:

L6SUECB



LTUB60 ACC. SUR END COVER BK.



Product code:

L6SUECW



LTUB60 ACC. SUR END COVER WH.



Product code:

L6SUECW3

Description:

LTUB60 ACC. SUR END COVER WE.



Product code:

L6SUECW4

Description:

LTUB60 ACC. SUR END COVER BS.