LAMPTUB 60 SUSP. CEILING ROSE


L61SE168MOIO930NB

LTUB60 SU RE 1680 7300 WW D/I OPAL BK

Description:

Surface mounted luminaire Lamptub 60 from LAMP. Made of recycled aluminium extrusion with circular section of 60mm and length of 1680mm. Direct-indirect light model with opal polycarbonate diffuser. Model for MID-POWER LED, with colour temperature 3000K with CRI90. Built-in electronic ON/OFF control gear. With IP40, IK07 degree of protection. Insulation class I / II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.

Finish: Matte black RAL 9011




Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output:	4.479 lm	⁰K :	3000
Plum:	52,5W	CRI :	90
Efficacy:	85,3 lm/w	R9 :	64
Туре:	MID POWER LED	MacAdam:	3
LED Lifetime:	72.000 L80 B10 (Ta=25⁰C)	Power Supply:	220-240V 50/60Hz
Power:	58.1W	Gear:	Electronic

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:



LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es Worktitude for light


LAMPTUB 60 SUSP. CEILING ROSE

L61SE168MOIO930NB

LTUB60 SU RE 1680 7300 WW D/I OPAL BK



PHOTOMETRIC DATA :





LAMPTUB 60 SUSP. CEILING ROSE

ACCESORIES :

Assembly



Product code: L6SUECB

Description: LTUB60 ACC. SUR END COVER BK.



Product code: L6SUECW

Description: LTUB60 ACC. SUR END COVER WH.

Worktitude for light



Product code: L6SUECW3

Description: LTUB60 ACC. SUR END COVER WE.



Product code: L6SUECW4

Description: LTUB60 ACC. SUR END COVER BS.