#### LAMPTUB 60 SUSP. CEILING ROSE



#### L61SE168MOIO940DB




## LTUB60 SU RE 1680 7600 NW D/I OP DALI BK

#### Description:

Surface mounted luminaire Lamptub 60 from LAMP. Made of recycled aluminium extrusion with circular section of 60mm and length of 1680mm. Direct-indirect light model with opal polycarbonate diffuser. Model for MID-POWER LED, with colour temperature 4000K with CRI90. Built-in electronic DALI control gear. With IP40, IK07 degree of protection. Insulation class I / II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.

Finish: Matte black RAL 9011



Installation: Suspended

#### **TECHNICAL SPECIFICATIONS:**

Light output: 4.623 lm °K: 4000 Plum: 52,5W CRI: 90 Efficacy: 88 lm/w 70 R9: Type: MID POWER LED MacAdam: 3

LED Lifetime: 72.000 L80 B10 (Ta=25°C) Power Supply: 220-240V 50/60Hz Gear: Power: 58.1W Adjustable DALI

## Light output tolerance +/- 10%





























## **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU













## LAMPTUB 60 SUSP. CEILING ROSE





L61SE168MOIO940DB


# LTUB60 SU RE 1680 7600 NW D/I OP DALI BK


## **PHOTOMETRIC DATA:**


L61SE168MOIO940DB  $\eta$  = 100% lmax = 269 cd/klmUTE: 0,69E + 0,31T CIE: 50 81 97 69 100
















# LAMPTUB 60 SUSP. CEILING ROSE



# ACCESORIES:

## **Assembly**



Product code:

L6SUECB



LTUB60 ACC. SUR END COVER BK.



Product code:

L6SUECW



LTUB60 ACC. SUR END COVER WH.



Product code:

L6SUECW3

Description:

LTUB60 ACC. SUR END COVER WE.



Product code:

L6SUECW4

Description:

LTUB60 ACC. SUR END COVER BS.