#### LAMPTUB 60 SUSP. CEILING ROSE



#### L61SE168MOOC927NB




# LTUB60 SU RE 1680 4800 VWW COMF BK

#### Description:

Surface mounted luminaire Lamptub 60 from LAMP. Made of recycled aluminium extrusion with circular section of 60mm and length of 1680mm, an opal comfort diffuser made of a translucent polycarbonate diffuser and an optical film to achieve a controlled light distribution and low UGR<19. Model for MID-POWER LED, with colour temperature 2700K with CRI90. Built-in electronic ON/OFF control gear. With IP40, IK07 degree of protection. Insulation class I / II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.

Finish: Matte black RAL 9011



Installation: Suspended

#### **TECHNICAL SPECIFICATIONS:**

Light output: 2.717 lm °K: 2700 Plum: 34,7W CRI: 90 Efficacy: 78,3 lm/w R9: 57 UGR: MacAdam: 3

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 72.000 L80 B10 (Ta=25°C) Gear: Electronic

Power:

## Light output tolerance +/- 10%





































# **CUSTOM MADE OPTIONS:**











Data according to regulations 2019/2020/EU and 2019/2015/EU













# LAMPTUB 60 SUSP. CEILING ROSE




L61SE168MOOC927NB


# LTUB60 SU RE 1680 4800 VWW COMF BK


## **PHOTOMETRIC DATA:**


L61SE168MOOC927NB  $\eta$  = 100% Imax = 663 cd/klm UTE: 1,00C


CIE: 66 90 99 100 100



















# LAMPTUB 60 SUSP. CEILING ROSE



# ACCESORIES:

# **Assembly**



Product code:

L6SUECB



LTUB60 ACC. SUR END COVER BK.



Product code:

L6SUECW



LTUB60 ACC. SUR END COVER WH.



Product code:

L6SUECW3

Description:

LTUB60 ACC. SUR END COVER WE.



Product code:

L6SUECW4

Description:

LTUB60 ACC. SUR END COVER BS.