LAMPTUB 60 SUSP. CEILING ROSE



L61SE168MOOP927DW

LTUB60 SU RE 1680 4800 VWW OPAL DALI WH



Description:

Surface mounted luminaire Lamptub 60 from LAMP. Made of recycled aluminium extrusion with circular section of 60mm and length of 1680mm, with opal polycarbonate diffuser. Model for MID-POWER LED, with colour temperature 2700K with CRI90. Built-in electronic DALI control gear. With IP40, IK07 degree of protection. Insulation class I / II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.



Finish: Matte white RAL 9010

Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output: 2.936 Im °K: 2700 Plum: 34,7W CRI: 90 Efficacy: 84,6 lm/w R9: 57 Type: MID POWER LED MacAdam: 3

LED Lifetime: 72.000 L80 B10 (Ta=25°C) Power Supply: 220-240V 50/60Hz Gear: Power: 30.3W Adjustable DALI

Light output tolerance +/- 10%





























CUSTOM MADE OPTIONS:















LAMPTUB 60 SUSP. CEILING ROSE





L61SE168MOOP927DW


LTUB60 SU RE 1680 4800 VWW OPAL DALI WH


PHOTOMETRIC DATA:


L61SE168MOOP927NW η = 100% lmax = 390 cd/klmUTE: 1,00E + 0,00T CIE: 50 81 97 100 100















LAMPTUB 60 SUSP. CEILING ROSE



ACCESORIES:

Assembly



Product code:

L6SUECB



LTUB60 ACC. SUR END COVER BK.



Product code:

L6SUECW

Description:

LTUB60 ACC. SUR END COVER WH.



Product code:

L6SUECW3

Description:

LTUB60 ACC. SUR END COVER WE.



Product code:

L6SUECW4

Description:

LTUB60 ACC. SUR END COVER BS.