
LAMPTUB 60 SURF. CEILING ROSE



L61SS084LOOC927N3

- LTUB60 SU SF 840 1300 VWW COMF WE



Description:

Surface mounted luminaire Lamptub 60 from LAMP. Made of recycled aluminium extrusion with circular section of 60mm and length of 840mm, an opal comfort diffuser made of a translucent polycarbonate diffuser and an optical film to achieve a controlled light distribution and low UGR<19. Model for MID-POWER LED, with colour temperature 2700K with CRI90. Built-in electronic ON/OFF control gear. With IP40, IK07 degree of protection. Insulation class I / II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.



Finish: Palette WELLBEING - 3 TEXTURED

Installation: Suspended

TECHNICAL SPECIFICATIONS:

 Light output:
 663 lm
 °K:
 2700

 Plum:
 9,7W
 CRI:
 90

 Efficacy:
 68,3 lm/w
 R9:
 57

 UGR:
 <19</td>
 MacAdam:
 3

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 72.000 L80 B10 (Ta=25°C) Gear: Electronic

Power: 8.5W

Light output tolerance +/- 10%









CUSTOM MADE OPTIONS:



















LAMPTUB 60 SURF. CEILING ROSE




L61SS084LOOC927N3


LTUB60 SU SF 840 1300 VWW COMF WE


PHOTOMETRIC DATA:


L61SS084LOOC927N3 η = 100% Imax = 665 cd/klm UTE: 1,00C


CIE: 66 90 99 100 100



















LAMPTUB 60 SURF. CEILING ROSE



ACCESORIES:

Assembly



Product code:

L6SUECB L



LTUB60 ACC. SUR END COVER BK.



Product code:

L6SUECW

Description:

LTUB60 ACC. SUR END COVER WH.



Product code:

L6SUECW3

Description:

LTUB60 ACC. SUR END COVER WE.



Product code:

L6SUECW4

Description:

LTUB60 ACC. SUR END COVER BS.