
LAMPTUB 60 SURF. CEILING ROSE



L61SS084LOOC940D4

LTUB60 SU SF 840 1300 NW COMF DALI BS



Description:

Surface mounted luminaire Lamptub 60 from LAMP. Made of recycled aluminium extrusion with circular section of 60mm and length of 840mm, an opal comfort diffuser made of a translucent polycarbonate diffuser and an optical film to achieve a controlled light distribution and low UGR<19. Model for MID-POWER LED, with colour temperature 4000K with CRI90. Built-in electronic DALI control gear. With IP40, IK07 degree of protection. Insulation class I / II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.



Finish: Palette BE SOCIAL - 4 TEXTURED

Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output: 720 lm °K: 4000 Plum: 9,7W CRI: 90 Efficacy: 74,2 lm/w 70 R9: UGR: <19 MacAdam: 3

Type: MID POWER LED Power Supply: 220-240V 50/60Hz LED Lifetime: 72.000 L80 B10 (Ta=25°C) Gear: Adjustable DALI

8.5W Power:

Light output tolerance +/- 10%



CLASE

























CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU











LAMPTUB 60 SURF. CEILING ROSE





L61SS084LOOC940D4


LTUB60 SU SF 840 1300 NW COMF DALI BS


PHOTOMETRIC DATA:


L61SS084LOOC940N4 η = 100% Imax = 665 cd/klm UTE: 1,00C


















LAMPTUB 60 SURF. CEILING ROSE



ACCESORIES:

Assembly



Product code:

L6SUECB L



LTUB60 ACC. SUR END COVER BK.



Product code:

L6SUECW

Description:

LTUB60 ACC. SUR END COVER WH.



Product code:

L6SUECW3

Description:

LTUB60 ACC. SUR END COVER WE.



Product code:

L6SUECW4

Description:

LTUB60 ACC. SUR END COVER BS.