LAMPTUB 60 SUSP. CEILING ROSE



L61SS084LOOC9TWD3

- LTUB60 SU SF 840 1200 TW COMF DALI WE



Description:

Surface mounted luminaire Lamptub 60 from LAMP. Made of recycled aluminium extrusion with circular section of 60mm and length of 840mm, an opal comfort diffuser made of a translucent polycarbonate diffuser and an optical film to achieve a controlled light distribution and low UGR<19. Model for MID-POWER LED, with TW colour temperature with CRI90. Built-in electronic DALI control gear. With IP40, IK07 degree of protection. Insulation class I / II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.



Finish: Palette WELLBEING - 3 TEXTURED

Dimensions: 847 x 67 x 80 mm

Installation: Suspended

TECHNICAL SPECIFICATIONS:

 Light output:
 905 lm
 ⁰K :
 TW

 Plum:
 12,1W
 CRI :
 90

 Efficacy:
 74,8 lm/w
 MacAdam:
 3

 UGR:
 <19</td>
 Power Supply:
 220-240V 50/60Hz

 Type:
 MID POWER LED
 Gear:
 Adjustable DALI DT8

LED Lifetime: 50.000 L80 B10 (Ta=25°C)

Power: 8.8W

Light output tolerance +/- 10%









CUSTOM MADE OPTIONS:



















LAMPTUB 60 SUSP. CEILING ROSE




L61SS084LOOC9TWD3


LTUB60 SU SF 840 1200 TW COMF DALI WE


PHOTOMETRIC DATA:


L61SS084LOOC9TWD3 η = 100% Imax = 663 cd/klm UTE: 1,00C


CIE: 66 90 99 100 100




















LAMPTUB 60 SUSP. CEILING ROSE



ACCESORIES:

Assembly



Product code:

L6SUECB



LTUB60 ACC. SUR END COVER BK.



Product code:

L6SUECW

Description:

LTUB60 ACC. SUR END COVER WH.



Product code:

L6SUECW3

Description:

LTUB60 ACC. SUR END COVER WE.



Product code:

L6SUECW4

Description:

LTUB60 ACC. SUR END COVER BS.