#### LAMPTUB 60 SURF. CEILING ROSE



#### L61SS084LOOP927NB




## **LTUB60 SU SF 840 1300 VWW OPAL BK**

#### Description:

Surface mounted luminaire Lamptub 60 from LAMP. Made of recycled aluminium extrusion with circular section of 60mm and length of 840mm, with opal polycarbonate diffuser. Model for MID-POWER LED, with colour temperature 2700K with CRI90. Built-in electronic ON/OFF control gear. With IP40, IK07 degree of protection. Insulation class I / II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.

Finish: Matte black RAL 9011



Installation: Suspended

#### **TECHNICAL SPECIFICATIONS:**

Light output: 716 lm °K: 2700 Plum: 9,7W CRI: 90 Efficacy: 73,8 lm/w R9: 57 Type: MID POWER LED MacAdam: 3

LED Lifetime: 72.000 L80 B10 (Ta=25°C) Power Supply: 220-240V 50/60Hz

Gear: Power: 8.5W Electronic

## Light output tolerance +/- 10%



CLASE





























# **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU













## LAMPTUB 60 SURF. CEILING ROSE





L61SS084LOOP927NB


## **LTUB60 SU SF 840 1300 VWW OPAL BK**


## **PHOTOMETRIC DATA:**


L61SS084LOOP927NB  $\eta$  = 100% lmax = 390 cd/klmUTE: 1,00E + 0,00T CIE: 50 81 97 100 100
















## LAMPTUB 60 SURF. CEILING ROSE



# ACCESORIES:

## **Assembly**



Product code:

L6SUECB



LTUB60 ACC. SUR END COVER BK.



Product code:

L6SUECW

Description:

LTUB60 ACC. SUR END COVER WH.



Product code:

L6SUECW3

Description:

LTUB60 ACC. SUR END COVER WE.



Product code:

L6SUECW4

Description:

LTUB60 ACC. SUR END COVER BS.