# LAMPTUB 60 SURF. CEILING ROSE

### L61SS084LOOP930D4

#### LTUB60 SU SF 840 1300 WW OPAL DALI BS

#### Description:

Surface mounted luminaire Lamptub 60 from LAMP. Made of recycled aluminium extrusion with circular section of 60mm and length of 840mm, with opal polycarbonate diffuser. Model for MID-POWER LED, with colour temperature 3000K with CRI90. Built-in electronic DALI control gear. With IP40, IK07 degree of protection. Insulation class I / II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.




Finish: Palette BE SOCIAL - 4 TEXTURED

Installation: Suspended

#### **TECHNICAL SPECIFICATIONS:**

Light output:	754 lm	⁰К:	3000
Plum:	9,7W	CRI :	90
Efficacy:	77,7 lm/w	R9 :	64
Туре:	MID POWER LED	MacAdam:	3
LED Lifetime:	72.000 L80 B10 (Ta=25°C)	Power Supply:	220-240V 50/60Hz
Power:	8.5W	Gear:	Adjustable DALI

### Light output tolerance +/- 10%



## **CUSTOM MADE OPTIONS:**




Worktitude for light


## LAMPTUB 60 SURF. CEILING ROSE

L61SS084LOOP930D4

LTUB60 SU SF 840 1300 WW OPAL DALI BS









## LAMPTUB 60 SURF. CEILING ROSE

## ACCESORIES :

## Assembly



Product code: L6SUECB

Description: LTUB60 ACC. SUR END COVER BK.



Product code: L6SUECW

Description: LTUB60 ACC. SUR END COVER WH.

Worktitude for light



Product code: L6SUECW3

Description: LTUB60 ACC. SUR END COVER WE.



Product code: L6SUECW4

Description: LTUB60 ACC. SUR END COVER BS.