LAMPTUB 60 SURF. CEILING ROSE



L61SS084MOOC940DW

LTUB60 SU SF 840 2600 NW COMF DALI WH



Description:

Surface mounted luminaire Lamptub 60 from LAMP. Made of recycled aluminium extrusion with circular section of 60mm and length of 840mm, an opal comfort diffuser made of a translucent polycarbonate diffuser and an optical film to achieve a controlled light distribution and low UGR<19. Model for MID-POWER LED, with colour temperature 4000K with CRI90. Built-in electronic DALI control gear. With IP40, IK07 degree of protection. Insulation class I / II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.



Finish: Matte white RAL 9010

Installation: Suspended

TECHNICAL SPECIFICATIONS:

Light output: 1.476 lm °K: 4000 Plum: 17,8W CRI: 90 Efficacy: 82,9 lm/w 70 R9: UGR: MacAdam: 3

Type: MID POWER LED Power Supply: 220-240V 50/60Hz LED Lifetime: 72.000 L80 B10 (Ta=25°C) Gear: Adjustable DALI

Power:

Light output tolerance +/- 10%



CLASE





























CUSTOM MADE OPTIONS:



















LAMPTUB 60 SURF. CEILING ROSE




L61SS084MOOC940DW


LTUB60 SU SF 840 2600 NW COMF DALI WH


PHOTOMETRIC DATA:


L61SS084MOOC940NW η = 100% Imax = 663 cd/klm UTE: 1,00C


CIE: 66 90 99 100 100



















LAMPTUB 60 SURF. CEILING ROSE



ACCESORIES:

Assembly



Product code:

L6SUECB L



LTUB60 ACC. SUR END COVER BK.



Product code:

L6SUECW

Description:

LTUB60 ACC. SUR END COVER WH.



Product code:

L6SUECW3

Description:

LTUB60 ACC. SUR END COVER WE.



Product code:

L6SUECW4

Description:

LTUB60 ACC. SUR END COVER BS.