### LAMPTUB 60 SURF. CEILING ROSE



### L61SS084MOOP930D3

LTUB60 SU SF 840 2500 WW OPAL DALI WE



### Description:

Surface mounted luminaire Lamptub 60 from LAMP. Made of recycled aluminium extrusion with circular section of 60mm and length of 840mm, with opal polycarbonate diffuser. Model for MID-POWER LED, with colour temperature 3000K with CRI90. Built-in electronic DALI control gear. With IP40, IK07 degree of protection. Insulation class I / II. Group 0 photobiological safety. Lifetime: 72.000h L80 B10. Compatible with Lamp Nomadic system. Available finishes: White (RAL 9010), Black (RAL 9011), Wellbeing and BeSocial palette.



Palette WELLBEING - 3 TEXTURED Finish:

Installation: Suspended

### **TECHNICAL SPECIFICATIONS:**

Light output: 1.544 lm °K: 3000 Plum: 17,8W CRI: 90 Efficacy: 86,7 lm/w R9: 64 Type: MID POWER LED MacAdam: 3

LED Lifetime: 72.000 L80 B10 (Ta=25°C) Power Supply: 220-240V 50/60Hz Gear: Power: 15.1W Adjustable DALI

## Light output tolerance +/- 10%



CLASE



















## **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU











## LAMPTUB 60 SURF. CEILING ROSE





L61SS084MOOP930D3


## LTUB60 SU SF 840 2500 WW OPAL DALI WE


## **PHOTOMETRIC DATA:**


L61SS084MOOP930N3  $\eta$  = 100% lmax = 390 cd/klmUTE: 1,00E + 0,00T CIE: 50 81 97 100 100
















Data according to regulations 2019/2020/EU and 2019/2015/EU

## **LAMPTUB 60 SURF. CEILING ROSE**



# ACCESORIES:

## Assembly



Product code:

L6SUECB L



LTUB60 ACC. SUR END COVER BK.



Product code:

L6SUECW

Description:

LTUB60 ACC. SUR END COVER WH.



Product code:

L6SUECW3

Description:

LTUB60 ACC. SUR END COVER WE.



Product code:

L6SUECW4

Description:

LTUB60 ACC. SUR END COVER BS.